according to Regulation (EG) Nr. 1907/2006 (changed by Regulation (EU) Nr. 453/2010)



1

INMAFEED K1008, K1010, K1013 Aluminia Injection Moulding Feedstock

Print date: 10.04.2013 Product code:

1. Identification of the substance/preparation and of the company/undertaking

Identification of the substance or preparation:

INMAFEED K1008, K 1010, K1013 Alumina Injection Moulding Feedstock

Use of the substance/preparation:

Use for ceramic injection moulding

Company/undertaking identification

Company name: INMATEC Technologies GmbH

Street: Heerstrassenbenden 11
Place: D-53359 Rheinbach

Phone: +49-2226-9087-0

Responsible Department: INMATEC Technologies GmbH

Quality management, job safety

Phone: 02226/9087-30 + 53

Emergency telephone: +49-2226-9087-0 (08:00 - 17:00h)

2. Hazards identification

Classification

The preparation is not dangerous in the sense of Directive 1999/45/EC.

3. Composition/information on ingredients

Chemical characterization (Mixture)

Hazardous components

EC-No.	CAS-No.	Chemical name	Quantity	Classification
215-691-6	1344-28-1	Aluminiumoxid 96-99.9 %	80 - 85 %	
	25322-68-3 68441-17-8	Combination based on polymers	15 - 20 %	

Full text of each relevant R phrase can be found in Section 16

Further Information

The preparation is not dangerous in the sense of Directive 1999/45/EC.

4. First aid measures

General information

In case of accident or if you feel unwell, seek medical advice immediately (show safety data sheet if possible.

After inhalation

Provide fresh air. In case of irritation of the respiratory tract seek medical advice. In case of allergic symptoms especially in the breathing area, seek medical advice immediately.

After contact with skin

In case of skin irritation consult a doctor. After contact with skin, wash immediately with water and soap.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

Revisions-Nr.: 1.20

according to Regulation (EG) Nr. 1907/2006 (changed by Regulation (EU) Nr. 453/2010)



2

INMAFEED K1008, K1010, K1013 Alumina Injection Moulding Feedstock

Print date: 10.04.2013 Product code:

After ingestion

Rinse mouth thoroughly with water. Let water be swallowed in little sips (dilution effect). Do not induce vomiting.

5. Fire-fighting measures

Suitable extinguishing media

Extinguishing materials should be selected according to the surrounding area. Water fog. Carbon dioxide (CO2). Extinguishing powder. Foam.

Extinguishing media which must not be used for safety reasons

High power water jet.

Special exposure hazards arising from substance or preparation itself, combustion products, resulting gases

Can be released in case of fire: Carbon monoxide (CO). Carbon dioxide (CO2).

Special protective equipment for fire-fighters

Wear a self-contained breathing apparatus and chemical resistant suit.

6. Accidental release measures

Personal precautions

Provide adequate ventilation.

Avoid generation of dust. Do not breathe dust.

Wear personal protection equipment. (Refer to chapter 8).

Environmental precautions

Dumpint into the environment must be prevented.

Methods for cleaning up/taking up

Collect in closed containers for disposal. Avoid generation of dust. Wash with generous amount of water.

7. Handling and storage

Handling

Advice on safe handling

Wear suitable protective clothing (Refer to chapter 8).

Advice on protection against fire and explosion

Please note: Usual measures für fire prevention.

Product is Combustible

Under certain conditions dust explosible; Fire-class B

Further information on handling

Conditions to avoid: Avoid generation of dust.

Storage

Requirements for storage rooms and vessels

Keep/Store only in original container. Keep container tightly closed. Do not store at temperatures over 30 $^{\circ}$ C.

Advice on storage compatibility

Do not store together with:

Sodium nitrate, oxygen difluoride, chlorine trifluoride, ethylene, fluorine; Vinyl acetate,

hydrogen halides, chlorinated hydrocarbons

Revisions-Nr.: 1.20

according to Regulation (EG) Nr. 1907/2006 (changed by Regulation (EU) Nr. 453/2010)



3

INMAFEED K1008, K1010, 1013 Alumina Injection Moulding Feedstock

11

Print date: 10.04.2013 Product code:

Further information on storage conditions

Protect from moisture Storageclass (VCI):

8. Exposure controls / personal protection

Exposure limit values

Exposure limits (EH40)

CAS-No.	Chemical name	mi/m³	mg/m³	F/m³	Category	Origin
					TWA (8 h)	AGW
1344-28-1	Aluminiumoxid 96 - 99.9 %		3		STEL 15min)	AGW

Exposure controls

Occupational exposure controls

Avoid contact with skin, eye and clothing

Protective and hygiene measures

Always close containers tightly after the removal of product.

Respiratory protection

Respiratory protection required in case of:

exceeding critical value

Suitable respiratory protective equipment:

Combination filter device (DIN EN 141). Filtertyp: B-P2/P3

Hand protection

Pull-over gloves of rubber. DIN EN 374.

Suitable material:

CR (polychloroprenes, Chloroprene rubber) - 0.5mm

NBR (Nitrile rubber) - 0.35mm FKM (fluororubber) - 0.4mm PVC (Polyvinyl chloride) - 0,5mm

Butyl rubber - 0.5mm

Eye protection

Suitable eye protection. Tightly sealed safety glasses. DIN EN 166

9. Physical and chemical properties

General Information

Physical state: granules (solid)
Colour: white to light greyish

Odour: faint

10. Stability and reactivity

Conditions to avoid

Keep away from heat. Decomposition takes place from temperatures above: 150° C Exothermic decomposition between 150 - 170°C

Materials to avoid

Sodium nitrate, oxygen difluoride, chlorine trifluoride, ethylene, fluorine, Vinyl acetate, hydrogen halides, chlorinated hydrocarbons

Revisions-Nr.: 1.20

according to Regulation (EG) Nr. 1907/2006 (changed by Regulation (EU) Nr. 453/2010)



INMAFEED K1008, K1010, K1013 Alumina Injection Moulding Feedstock

Print date: 10.04.2013 Product code:

Hazardous decomposition products

Can be released in case of fire: Carbon monoxide (CO). Carbon dioxide (CO2).

11. Toxicological information

Acute toxicity

Acute toxicity, oral rat. LD50: >15000 mg/kg
Irritant effect on the eye: Not an irritant
Irritant effect on the skin: Not an irritant

12. Ecological information

Ecotoxicity

Acute fish toxicity: LC50>10g/l
Bacterial toxicity: EC0>1.000mg/l
Methode: OECD 209

Persistence and degradability

Product is biodegradable with difficulty.

Method: Zahn-Wellens-Test

Further information

Elimination occurs essentially by mechanical separation or ultrafiltration

13. Disposal considerations

Advice on disposal

Waste disposal according to official state regulations. Consult the local waste disposal expert about waste disposal.

Waste disposal number of waste from residues / unused products

060316 WASTES FROM INORGANIC CHEMICAL PROCESSES;

wastes from the MFSU of salts and their solutions and metallic oxides; metallic oxides other than those mentioned in 060315

Contaminated packaging

Cleaned containers may be recycled.

14. Transport information

Land transport (ADR/RID)

UN-number: Not restricted

Warning plate

Description of the goods

Not restricted

Inland waterways transport

UN-number: Not restricted

Description of the goods

Not restricted

Marine transport

UN-number: Not restricted

Description of the goods

Not restricted

Revisions-Nr.: 1.20

according to Regulation (EG) Nr. 1907/2006 (changed by Regulation (EU) Nr. 453/2010)



INMAFEED K1008, K1010, K1013 Alumina Injection Moulding Feedstock

Print date: 10.04.2013 Product code:

Air transport

UN/ID number: Not restricted

Description of the goods

Not restricted

15. Regulatory information

Labelling

S phrases Do not breathe dust.

National regulatory information

Water contaminating class (D): 1-slightly water contaminating

16. Other information

Further information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Changes

Rev.: 1.2 Revision

The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet).

INMATEC Technologies GmbH
Heerstrassenbenden 10, D-53359 Rheinbach
www.inmatec-gmbh.com,
info@inmatec-gmbh.com

Geschäftsführer: Dr. Moritz von Witzleben Amtsgericht bonn HRB 12582

Ust-Identnr.: DE230418018, St.Nr. 222/5708/1896



Dresdner Bank AG

Kto: 2 135 942 00 - BLZ: 370 800 40 IBAN DE56 3708 0040 0213 5942 00 SWIFT/BIC Code: DRES DE FF 380

Commerzbank

Kto: 324 999 200 - BLZ: 380 400 07

Kölner Bank

Kto: 930 354 007 - BLZ: 371 600 87

Revisions-Nr.: 1.20